

pulsar
NS125



SOLE DISTRIBUTOR FOR NEPAL
Hansraj Hulaschand & Co Pvt. Ltd.
Teku Road, Kathmandu, Ph. No: 5330001/5368088
url: nepal.globalbajaj.com/en

[/PulsarNepal](#)

[/PulsarNepal](#)

[/Company/Golchhagroup](#)

FOR MORE INFORMATION ABOUT YOUR
NEAREST DEALER PLEASE CONTACT

Bajaj 24 x 7
HELPLINE 166001 75555
98015 75555



INTRODUCING THE ALL-NEW
pulsar
NS125
A 125cc LIKE NEVER BEFORE!

BSVI

LATEST BS6 COMPLIANT





pulsar NS125

TECHNICAL SPECIFICATIONS

ENGINE & TRANSMISSION

Type : 4 Stroke, Single cylinder, Air cooled
Bore X Stroke : 52 mm X 58.6 mm
Displacement : 124.45 cc
Idling speed : 1300 +/- 100 rpm
Max. Net Power : 12 PS @ 8500 rpm
Max. Net Torque : 11 Nm @ 7000 rpm
Ignition system : DC
Spark plugs : 2 nos.
Engine lubrication : Wet sump forced lubrication
Transmission : 5 speed (1 Down 4 up)

CHASSIS & BODY

Frame : Perimeter Frame
Suspension : Front : Telescopic Fork
Rear : Monoshock-with Nitrox
Brakes : CBS
Front : Disc, Ø 240 mm
Rear : Drum, Ø 130 mm
Tyres : Front : 80/100-17, Tubeless
Rear : 100/90-17, Tubeless
Tyre Pressure : Front : 1.75 Kg/cm² (25 PSI)
Rear (Solo) : 2.00 Kg/cm² (28 PSI)
Rear (Pillion) : 2.25 Kg/cm² (32 PSI)
Fuel Tank Capacity : Full : 12 Litres
Usable Reserve : 2.57 Litres
Un-usable Reserve : 0.24 Litre
Length : 2012 mm
Width : 810 mm
Height : 1078 mm
Wheel Base : 1352 mm
Ground Clearance : 178 mm
Vehicle Kerb Weight : 141 kg

AVAILABLE IN

FIERY ORANGE

BURNT RED

BEACH BLUE

PEWTER GREY